

Herakulix[®] M

TECHNISCHES DATENBLATT



*optionales Zubehör MLRZ

Art. Nr.	VE	SIHGA [®] Herakulix [®] Type	Holzanschluss Type	Justierbereich		Bemessungswerte		Charakter. Werte**
				von	bis	Druckkraft [kN]	Querkraft [kN]	Zugkraft [kN]
51307	5	M RI 40	IdeFix [®] IFK 406	155	220	89,09	3,25	29,00
51317	5	M QI 40	IdeFix [®] IFK 406	155	220	89,09	3,25	29,00
51327	5	M RG	GoFix [®] S+ 8,0 x 125	155	220	89,09	-	10,90
51337	5	M QG	GoFix [®] S+ 8,0 x 125	155	220	89,09	-	10,90
51347	5	M BG	GoFix [®] S+ 8,0 x 125	137	202	89,09	3,20	10,90
47716	5	*MLRZ	Ring + Scheibe	M 27	Ø 50/28			

** charakteristische Werte für Bemessung nach EC 5 und Festigkeitsklasse C 24 (ρ_k 350 kg/m³)



DETAILS

- integrierter Neigungsausgleich bis ±5° in alle Richtungen
- zweiteiliges System mit geringem Einfahrweg
- Einsatz im bewitterten Bereich zulässig (NKL 3)
- ermöglicht individuelle Verankerung und unbehindert 90°-Bohren

ETA-18/0886

