

# TerrassenFix® II Set TFL

## TECHNICAL DATA SHEET



| SIHGA®<br>montagepack |     | Dimension<br>TerrassenFix® II | Planks<br>Thickness | Set - Screw<br>L-GoFix® MS | Sufficient<br>for approx. |
|-----------------------|-----|-------------------------------|---------------------|----------------------------|---------------------------|
| Art. No.              | PU  | Type                          | [mm]                | Ø x Length                 | [m²]                      |
| 40526                 | 100 | <b>TFL 60</b>                 | 20                  | 5,0 x 60                   | 7,5                       |
| 40546                 | 100 | <b>TFL 70</b>                 | 24                  | 5,0 x 70                   | 7,5                       |
| 40566                 | 100 | <b>TFL 80</b>                 | 28                  | 5,0 x 80                   | 7,5                       |
| 40576                 | 100 | <b>TFL 90</b>                 | 32                  | 5,0 x 90                   | 7,5                       |



### DETAILS

- TerrassenFix® II and L-GoFix® MS as a Set
- L-GoFix® MS made from hardened stainless steel
- The joint distance should not be less than 7 mm or 6% of the plank width.
- TerrassenFix® II from polyethylene, remains permanently dimensionally stable, is heat-, frost- and UV-resistant
- joint setting for 4, 5, 6, 7, 8, 9 mm wide joints without residue in the joint



TAKE THE BEST



Leitbetrieb Österreich  
Leitbetrieb Deutschland